

## Prepare Finger or Finger-Over-Finger Splices

The Pun M™ is designed to effortlessly punch fingers into polyurethane and PVC conveyor belts in preparation for installing vulcanized splices. The tool is available in 3 standard widths; 300 mm (12"), 600 mm (24") and 900 mm (36"). The open construction of the punch enables punching wider belts in multiple steps.



PUN M™

### Ideal for Working on Location

The Pun M is manually operated and does not need electricity or air pressure for its operation. The punching force of 50 kN (11,000 lbs.) is created by pulling the lever and is easily done with one hand by an average person. Because of its easy set-up and manual operation, the Pun M is an ideal tool for working on location, as well as in a workshop.



### Easy Operation

one hand clamping bar



### Flexible Configurations

for all types of finger punching



### Manually Operated

no electricity or air pressure needed



### Portable Equipment

for on-site use

## Other Novitool® Solutions:



*Aero® Press: An innovative, air-cooled press that does not require external components. Complete cycle time is approximately 10 minutes, significantly increasing belt productivity.*



*Ply 130™ Ply Separator: The robust design allows for quick, effortless, and precise ply separation on thermoplastic belts - even extremely thin or difficult belts.*

## NOVITool® PUN M™ Mobile Finger Punch

### Easy Operation

To punch a belt, one belt end is positioned against the end stop and then clamped in place. Precise fingers are quickly punched with each lever pull.

Pun M™ Dimensions				
	L	H	W	Weight
Pun M 300	570 mm 23"	370 mm 15"	360 mm 14"	14 kg 31 lbs
Pun M 600	870 mm 34"	370 mm 15"	360 mm 14"	17 kg 37 lbs
Pun M 900	1170 mm 46"	370 mm 15"	360 mm 14"	20 kg 44 lbs

Pun M™ Ordering Information	
Model	Item Code
PUN-M-300	08016
PUN-M-600	08017
PUN-M-900	08018

### Punch Types

Depending on the desired finger dimensions, Flexco offers a variety of punchboards for the Novitool Pun M™. Please note that punchboards are supplied separately. When ordering a new tool please state the desired punchboard (s).

Pun M™ Punchboard Specifications	
Pun M Width	Ordering Number
<b>50 x 20 mm (1.97" x 0.79")</b> (also suitable for Finger-Over-Finger splices)	
300 mm (12")	PUN-B-50x20-300
600 mm (24")	PUN-B-50x20-600
900 mm (36")	PUN-B-50x20-900
<b>70 x 15 mm (2.76" x 0.59")</b>	
300 mm (12")	PUN-B-70x15-300
600 mm (24")	PUN-B-70x15-600
900 mm (36")	PUN-B-70x15-900
<b>80 x 20 mm (3.15" x 0.79")</b>	
300 mm (12")	PUN-B-80x20-300
600 mm (24")	PUN-B-80x20-600
900 mm (36")	PUN-B-80x20-900



*Manual punching - operates with one hand*



*Punches precise fingers*



*Easy positioning and clamping*



2525 Wisconsin Avenue • Downers Grove, IL 60515-4200 U.S.A.  
Tel: (630)-971-0150 • Fax: (630)-971-1180 • E-mail: info@flexco.com • Web: [www.flexco.com](http://www.flexco.com)

Australia: 61-2-9680-3322 • China: 86-21-33528388 • England: 44-1274-600-942  
Germany: 49-7428-9406-0 • Mexico: 52-55-5674-5326 • South Africa: 27-11-608-4180

©2009 Flexible Steel Lacing Company. Novitool® is a registered trademark. ENMV1g - For Reorder: X2224

**LABRİS MAD.VE SAN.LTD.ŞTİ.**

İncek Yolu Taşpınar Mah.No.473 ince-06837-Ankara-Türkiye  
Tel. + 90 312 499 32 55 (pbx) • Faks + 90 312 499 33 35 • e-mail: info@labrisltd.com.tr • [www.labrisltd.com.tr](http://www.labrisltd.com.tr)

Authorized Distributor:

